



Undercounter Chiller
MODEL AP-UCC-3S-KIT
Undercounter Water Chiller

Enjoy Chilled Water on Tap



**Separate
Chilled
Water
Dispensing
Tap
required**

See back for details
Can also use dual
temperature Instant
hot faucets as shown

Include our Alwaysfreshh2o High Flow (1.5 gpm flow rate) &
High Performance Chemical Reduction Drinking Water System
Model HFC 1000

for Freshly filtered & chilled water for drinking, cooking, ice, and more!
This system is designed to be installed inline to existing cold sink faucet
to provide
filtered water to the chiller and filtered water from your
existing cold sink faucet too!

Also includes installation materials to complete most undercounter installations:

- 10 feet of 1/4" tubing
- AP-IK-CP-I4 installation kit
- 1/4" Inlet/Outlet fittings





CHILLER SPECIFICATIONS AND PERFORMANCE DATA

Material:

- Case-Powder coated steel
- Cold water tank stainless steel

Electrical

- Power rating Single phase (100-115V 60Hz)
- Power cord: 3 wire w/ground
- Standard current 1.2A
- Locked rotor amps (LRA) = 5.1A
- Power 75W

Electrical Compressor

- Single phase motor
- Refrigerant R-134a (ozone friendly)
- Rfrigerant Charge: 30g
- Capacity 11.5 l/hr (3.0 gal/hr) (dependent on ambient temp)
- Cool water outlet temp: 45 degree F +/- 2 degree F
- Thermostat preset at factory (field adjustable)
- Hermetically sealed, PTC starter with overload protector

Product details:

- Product weight 13.3kg (29.3 lb)
- Product boxed weight 14.6kg (32.5 lb)
- Product dimensions 16.1"(W) X 11.8"(D) X 11.8"(H)
- Product boxed dimensions 17.3"(W) X 13.0"(D) X 13.4"(H)
- Applicable Standards: UL-399 and CSA-C22.2, No. 120-M91
- Certifications: CE, UL, CSA

SUGGESTED WATER FILTRATION SYSTEM Alwaysfreshh2o model HFC-1000

Our high flow drinking water system can be connected to this chiller and other water using locations - such as an instant hot tap, ice maker, pot filler, **even your existing cold sink faucet.**

Enjoy great tasting, healthful water and appliance protection with our built-in limescale feature.



IMPORTANT PRODUCT FEATURES

Dispensing Chilled Water

A separate dispensing faucet is suggested/required

Quick Recovery

3 gallon per hour highest in industry

Large compressor Surface Area

Keeps unit running efficiently

Compact Size

Fits most 36" w base cabinets

Whisper Quiet

Ventilation

Minimum of 5" clearance each side recommended

Unit may require additional venting of base cabinet

Low electrical usage

Only 2 amp operating

Suggest dedicated circuit of 15 or 20 amp

Cold water only Dispensing faucets

Classic

Victoria

Designer



Dual Temperature Instant Hot System Dispensing faucets

Contemporary

Victoria

Traditional



Note: These faucets require the instant hot tank to complete system



961 N. Main St, Mansfield, OH 44903
 phone: (800)522-3949 fax: (419)529-8484
 web site: www.alwaysfreshh2o.com
 email: waterline@alwaysfreshh2o.com